

# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

C200-PLUS Ultrabond, Comp. A

UFI: 430J-515M-K20Y-6UYD

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: Sympafix
Street: Fluorietweg 25e
Place: NL-1812 RR Alkmaar
Telephone: +31 1804 68114
e-mail: office@sympafix.com

**1.4. Emergency telephone** +49 (0)551-19240 (GIZ-Nord, German and English 24/7)

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Skin Sens. 1: H317

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# **GB CLP Regulation**

# Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol

Signal word: Warning

Pictograms:



## **Hazard statements**

H317 May cause an allergic skin reaction.

# **Precautionary statements**

P261 Avoid breathing vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

# 2.3. Other hazards

No information available.



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 2 of 11

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulat	ion)			
2082-81-7	Tetramethylene dimethacrylate			15 - < 20 %	
	218-218-1		01-2119967415-30		
	Skin Sens. 1B; H317				
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			< 1 %	
	248-666-3		01-2119490226-37		
	Eye Irrit. 2, Skin Sens. 1; H319	H317			
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-o			< 1 %	
	254-075-1		01-2119980937-17		
	Acute Tox. 2, Eye Irrit. 2, Aquat	ic Chronic 3; H300 H319 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
2082-81-7	218-218-1	218-218-1 Tetramethylene dimethacrylate	
	dermal: LD50	dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 1 %
	dermal: LD50	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 1 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

## After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

# 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.





according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 3 of 11

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

## Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### **Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

## Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 4 of 11

Wash hands thoroughly after handling. When using do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

## Hints on joint storage

Do not use for products which come into contact with the food stuffs.

# Further information on storage conditions

storage temperature: 5 - 25°C

### 7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
2082-81-7	Tetramethylene dimethacrylate						
Worker DNEL	., long-term	inhalation	systemic	14,5 mg/m³			
Worker DNEL	., long-term	dermal	systemic	4,2 mg/kg bw/day			
Consumer DN	NEL, long-term	inhalation	systemic	4,3 mg/m³			
Consumer DN	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day			
Consumer DN	NEL, long-term	oral	systemic	2,5 mg/kg bw/day			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol						
Worker DNEL, long-term		inhalation	systemic	14,7 mg/m³			
Worker DNEL	., long-term	dermal	systemic	4,2 mg/kg bw/day			
Consumer DN	NEL, long-term	inhalation	systemic	8,8 mg/m³			
Consumer DN	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day			
Consumer DN	NEL, long-term	oral	systemic	2,5 mg/kg bw/day			
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol						
Worker DNEL, long-term		inhalation	systemic	2 mg/m³			
Worker DNEL, long-term		dermal	systemic	0,6 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	0,3 mg/kg bw/day			
Consumer DNEL, long-term		dermal	systemic	0,3 mg/kg bw/day			
Consumer DN	NEL, long-term	inhalation	systemic	0,4 mg/m³			



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 5 of 11

#### **PNEC values**

CAS No	Substance	
Environmer	ntal compartment	Value
2082-81-7	Tetramethylene dimethacrylate	
Freshwater		0,043 mg/l
Marine water	er	0,004 mg/l
Freshwater	sediment	3,12 mg/kg
Marine sedi	ment	0,312 mg/kg
Micro-organ	nisms in sewage treatment plants (STP)	2 mg/l
Soil		0,573 mg/kg
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater		0,904 mg/l
Marine water	er	0,904 mg/l
Freshwater	sediment	6,28 mg/kg
Marine sedi	ment	6,28 mg/kg
Micro-organ	nisms in sewage treatment plants (STP)	10 mg/l
Soil		0,727 mg/kg
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater		0,017 mg/l
Marine water	er	0,0017 mg/l
Freshwater sediment		0,0783 mg/kg
Marine sedi	ment	0,0072 mg/kg
Soil		0,005 mg/kg

## Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

#### 8.2. Exposure controls



## Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

# Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear eye/face protection.

### Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four





according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 6 of 11

control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty) Colour: light beige Odour: characteristic Odour threshold: No data available

#### Changes in the physical state

Melting point/freezing point: not determined Boiling point or initial boiling point and not determined

boiling range:

Flash point: not applicable

**Flammability** 

Solid/liquid: not determined Gas: not applicable not determined Lower explosion limits: Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined Gas: not applicable not determined Decomposition temperature: not determined pH-Value:

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined Density (at 20 °C): 1,77 g/cm<sup>3</sup> not determined Relative vapour density:

### 9.2. Other information

# Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

## Other safety characteristics

Solid content: not determined Evaporation rate: not determined



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 7 of 11

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

#### 10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name				
	Exposure route	Dose	Species	Source	Method	
2082-81-7	Tetramethylene dimethacrylate					
	oral	LD50 10066 mg/kg	Rat			
	dermal	LD50 > 3000 mg/kg	Rabbit			
27813-02-1	Methacrylic acid, mon	oester with propane-1	,2-diol			
	oral	LD50 > 2000 mg/kg	Rat			
	dermal	LD50 > 5000 mg/kg	Rabbit			
38668-48-3	1,1'-(p-Tolylimino)dipr	opan-2-ol				
	oral	LD50 > 25 - < 200 mg/kg	Rat			
	dermal	LD50 > 2000 mg/kg	Rat			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol)

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 8 of 11

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# **SECTION 12: Ecological information**

### 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name							
	Aquatic toxicity	Dose	Dose [h]   [d] Species S		Source	Method		
2082-81-7	Tetramethylene dimethacrylate							
	Acute algae toxicity	ErC50 mg/l	9,79	72 h				
	Crustacea toxicity	NOEC mg/l	5,09	21 d				
27813-02-1	Methacrylic acid, mon	oester with	propane-1,2	2-diol				
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h Pseudokirch subcapitata				
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h Daphnia ma water flea)	agna (Big			
	Algae toxicity	NOEC	mg/l					
38668-48-3	1,1'-(p-Tolylimino)dipr	opan-2-ol						
	Acute fish toxicity	LC50	17 mg/l	96 h Danio rerio	(zebrafish)			
	Acute algae toxicity	ErC50	245 mg/l	72 h Desmodesn subspicatus				
	Acute crustacea toxicity	EC50 mg/l	28,8	48 h Daphnia ma water flea)	agna (Big			
	Algae toxicity	NOEC mg/l	57,8	72 d Desmodesn subspicatus		OECD 201		

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name						
	Method Value d Source						
	Evaluation						
2082-81-7	Tetramethylene dimethacrylate						
	OECD 310	84 %	28				
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol						
	OECD 301C	81%	28				

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 9 of 11

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF 080409 COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND

> PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances:

hazardous waste

## List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### List of Wastes Code - contaminated packaging

WASTE PACKAGING: ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND 150110

> PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

# **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

# Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

# Marine transport (IMDG)



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 10 of 11

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

#### **Additional information**

VOC content: 0,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)





according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. A

Revision date: 26.10.2022 Page 11 of 11

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 4: Acute toxicity, Category 4

Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Corr. 1B: Skin corrosion/irritation, Category 1B

Skin Sens. 1: Skin sensitilization, Category 1 Skin Sens. 1B: Skin sensitilization, Category 1B

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

## Relevant H and EUH statements (number and full text)

H300 Fatal if swallowed.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

C200-PLUS Ultrabond, Comp. B

UFI: A50J-N1V0-W20G-U6JF

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

compound mortar B-component (hardener)

### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: Sympafix
Street: Fluorietweg 25e
Place: NL-1812 RR Alkmaar
Telephone: +31 1804 68114
e-mail: office@sympafix.com

1.4. Emergency telephone +49 (0)551-19240 (GIZ-Nord, German and English 24/7)

number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Skin Sens. 1: H317

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## **GB CLP Regulation**

#### Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



# **Hazard statements**

H317 May cause an allergic skin reaction.

# **Precautionary statements**

P261 Avoid breathing vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

### 2.3. Other hazards

No information available.



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 2 of 10

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name	Chemical name				
	EC No Index No REACH No					
	Classification (GB CLP Regulation)					
94-36-0	Dibenzoyl peroxide			5 - < 10 %		
	202-327-6 617-008-00-0 01-2119511472-50					
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410					

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 10 %	
	oral: LD50 = > 5000 mg/kg M acute; H400: M=10 M chron.; H410: M=10			

#### **Further Information**

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

## After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

# After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

## 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Foam

Extinguishing powder





according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 3 of 10

Water spray jet Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

# Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

## Hints on joint storage

Do not store together with: Oxidising agent, strong



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 4 of 10

Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

storage temperature: 5 - 25°C

### 7.3. Specific end use(s)

see section 1.2

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m³

### **PNEC** values

CAS No	Substance	
Environment	al compartment	Value
94-36-0 Dibenzoyl peroxide		
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

## 8.2. Exposure controls



# Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Individual protection measures, such as personal protective equipment

# Eye/face protection

Wear eye/face protection.



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 5 of 10

## **Hand protection**

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: black

Odour: characteristic
Odour threshold: No data available

### Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not determined

boiling range:

Flash point: not applicable

**Flammability** 

Solid/liquid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined Gas: not applicable
Decomposition temperature: not determined pH-Value: not determined
Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

1,77 g/cm³

Relative vapour density:

not determined

not determined

# 9.2. Other information



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 6 of 10

### Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

## Other safety characteristics

Solid content: not determined Evaporation rate: not determined

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

see section 10.3

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

#### 10.4. Conditions to avoid

see section 7.2

#### 10.5. Incompatible materials

Oxidising agent, strong

### 10.6. Hazardous decomposition products

Benzoic acid Benzene

**Biphenyl** 

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].



according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 7 of 10

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus )

IC10: (0 - 72h) = 60 mg/lIC50: (0 - 72h) = > 500 mg/l

OECD 202 (Daphnia magna (Big water flea))

EC0/NOEC (48h) = 100 mg/l EC50 (48h) = > 500 mg/l EC100 (48h) = >> 500 mg/l

OECD 203 (Danio rerio (zebrafish))

LC0/NOEC = 500 mg/l LC50 = > 500 mg/l LC100 = >>500 mg/l

	o oo mga						
CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide						
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 mg/l	0,11		Daphnia magna (Big water flea)	OECD 202	
	Algae toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201	
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211	
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209	

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD crite	ria).		

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

## 12.4. Mobility in soil

The product has not been tested.

## 12.5. Results of PBT and vPvB assessment



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 8 of 10

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - used product

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF 080409 COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

# List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING: ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED: packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances: hazardous waste

## **SECTION 14: Transport information**

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

### Mari

arine transport (IMDG)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.





according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 9 of 10

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

**Additional information** 

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

## Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%



# **Safety Data Sheet**

according to UK REACH Regulation

# C200-PLUS Ultrabond, Comp. B

Revision date: 26.10.2022 Page 10 of 10

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Acute Tox. 2: Acute toxicity, Category 2

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

#### Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)